

# 8-8114 UNIVERSAL 100W DASH / REMOTE SIREN

- Suitable for dash mount or separate remote mount
- All hardware for dash and remote mount included.
- 2 x integral 10A auxillary control switches (for lights etc)
- Variable siren volume versions with programmable minimum volume setting.
- Non destructive reverse polarity protection
- Ambient temperature range -20°C to +50°C



Rugged heavy duty removable connectors ensure ease of installation. Connector design prevents incorrect insertion.



4 Tone rotary selector switch & momentary rocker switch for air horn or siren.



Radio rebroadcast switch & 2 x 10A rated switches for controlling external equipment e.g. lights.



Volume control for PA volume or PA and siren volume depending on model selected



- Designed for combined dash mount or separated remote mount.
- Front panel is easily separated allowing amplifier to be remote mounted. All hardware for combined and separate mounting is supplied as standard, including extended (5 Metre) data cable to connect between the amplifier and control panel when remote.
- Other included functions include intelligent horn ring transfer to activate siren and change tones using the vehicle horn signal. Can be configured to disable the normal vehicle horn operation when siren is in active.
- A / B mode switch allows horn to select next tone or provide a brief (5 second) tone change - ideal for use at junctions and obstructions.
- Siren includes an optional interlock function to prevent the siren from operating unless warning lights are also operating.
- Automatic over voltage protection - reduces siren power to compensate for overvoltage, avoiding speaker damage

Dimensions:		Weight:
Combined unit (excl buttons) 141mmW x 175mmD x 45mmH		Siren amplifier 1.1KG
Controller only (excl buttons) 141mmW x 29mmD x 45mmH		Shipping weight (inc looms etc) 2.3KG
Order code	Description	
8-8114-12	12V 100W siren, dash or remote mount with variable PA volume	
8-8114-V-12	12V 100W siren, dash or remote mount, variable PA and siren tone volume (programmable minimum siren tone value)	
8-8114-24	24V 100W siren, dash or remote mount with variable PA volume	
8-8114-V-24	24V 100W siren, dash or remote mount, variable PA and siren tone volume (programmable minimum siren tone value)	